

UNIFLEX[®]

Greased Crimper Program

Why Grease?

For beginners, one-time users, small workshops, etc., these crimpers, which afford you the quality and precision UNIFLEX machines are renowned for, are just one step away from a greaseless crimper.

With UNIFLEX, UNIFLEX is re-introducing a high-tolerance crimper using older technology that is commonly used in the market today. UNIFLEX is offering these crimpers of the highest quality as a way to support and help you grow your business and connect you to the full line-up of UNIFLEX products.

All of the products in this leaflet are made in Germany, and sold and serviced all over the world through our UNIFLEX branches.

UNIFLEX.de

made in Germany



GERMANY

UNIFLEX-Hydraulik GmbH
Robert-Bosch-Strasse 50-52
61184 Karben/Germany

+49 60 399 171 0
+49 60 399 1711 181
+49 174 7641 526
sales@uniflex.de

USA

UNIFLEX of America LLC
1088 National Parkway
60173 Schaumburg, IL/USA

+1 847 519 11 00
+1 847 519 11 04
sales@uniflex.de

URUGUAY

UNIFLEX Latin America Srl
Saint Bois 5074
Free zone Stock
Montevideo, UY 12000/Uruguay

+598 2 7120 660 ext. 1115
+598 2 7120 660 ext. 2101
sales@uniflex.de

INDIA

Uniflex Hose Assembly Machines India
Pvt. Ltd.
Plot No. 588/627, Rect.No. 33, Kila No. 19
Pataudi Road, Kadipur Industrial Area
122001 Gurgaon India

+91 91 7982219100
+91 99 11224090
+91 91 7982219100
dinesh.kumar(at)
uniflex.de

CHINA

UNIFLEX-Hydraulik Trading (Shanghai)
Co.
South 2 Warehouse, Building 1
No. 500 Jianyun Road
Zhoupu Town, Pudong New Area
Shanghai CN 201318/China

+86 21 5032 7022
sales@uniflex.de

SINGAPORE

UNIFLEX-Hydraulik
Asia Pacific Pte. Ltd.
No. 51 Bukit Batok Crescent #07-25
658077 Singapore

+65 68 96 67 95
+65 68 96 64 28
sales@uniflex.de

JAPAN

UNIFLEX JAPAN
Representative office
1-20-3 Nishishinjuku, Shinjuku-ku
8F, Nishishinjuku Takagi Bldg.
Tokyo, JP 160-0023
Japan

+81 3 6890 3386
sales@uniflex.de

RUSSIA

Via partner company:
Hydraulics-Engineering-Services LLC
Ryabinina 31, Entrance 182
620149 Yekaterinburg
Sverdlovsk Oblast
Russian Federation

+7 343 227 88 83
sales@uniflex.de



UG 16 Ecoline

Technical data	UG 16 Ecoline
Crimp force (kN / Ton)	900/90
Greased machine	✓
Control	Control A
SAE R 12 / 4SH 1 piece fitting *	1"
SAE R15 / 4SH 2 piece fitting *	¾"
SAE R12 / 4SP 2 piece fitting *	1"
Industrial	1 ¼"
90° Elbows	1"
Crimp range	63 mm**
Opening	+ 22 mm
Opening without dies	77 mm
Master dies length (mm)	75 mm
Type of dies	263
Drive	manual
Oil	0,75 L
L x W x H (mm)	218 x 165 x 352
Weight	29 kg

Type of dies	
 263	
Ø mm	mm
6,8	40
9	75
12	75
14	75
17	75
20	75
24	75
28	75
32	75
36	75
40	75
44	75
47	75

* According to the fitting.

** With master dies.

Package



QDS 263 B


UG 16 Ecoline:

UG 16 Ecoline Package = Machine

+ PB Ø 17, 20, 24

+ QDS 26X B

Additional Information



An optical signal is given when the crimp measure is reached. The electric and pneumatic variants have an automatic stop function.



Telescopic hand-lever included.





UG 20 Ecoline



UG 20 Mobileline


Technical data	UG 20 Ecoline	UG 20 Mobileline
Crimp force (kN / Ton)	190	190
Greased machine	✓	✓
Control	Control A	Control A
SAE R 12 / 4SH 1 piece fitting *	1 ¼"	1 ¼"
SAE R15 / 4SH 2 piece fitting *	1 ¼"	1 ¼"
SAE R12 / 4SP 2 piece fitting *	1 ½"	1 ½"
Industrial	2"	2"
90° Elbows	1 ¼"	1 ¼"
Crimp range	70 mm	70 mm
Opening	+ 27 mm	+ 27 mm
Opening without dies	97 mm	97 mm
Master dies length (mm)	100 mm	100 mm
Type of dies	239-xx-Ø	239-xx-Ø
Speed (mm/sec)		
Close	2,0	1,5
Crimp	2,0	0,4
Open	7,6	5,7
Noise level	69 dBA	69 dBA
Drive	3 kW	1,8 kW
Oil	35 L	4 L
L x W x H (mm)	600 x 550 x 630	430 x 370 x 440
Weight	150 kg	110 kg
Options		
12 VDC / 24 VDC	–	✓
1-Phase	✓	✓
3-Phase	✓	–

* According to the fitting


Type of dies	
239-xx-Ø-yy	
Ø mm	-mm-
6,8	50
9	50
10	50
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

Package



QDS 239 B



QDC 239.5

Package = Machine

+ PB Ø 17, 20, 24, 28, 32, 40, 44, 50

+ QDC 239.5

+ QDS 239 B



UNIJOB UG 32: TECHNICAL DATA



UG 32 Mobileline



UG 32 Ecoline



UG 32 S


Technical data	UG 32 Mobileline	UG 32 Ecoline	UG 32 S
Crimp force (kN / Ton)	250	250	350
Greased machine	✓	✓	✓
Control	Control A	Control A	Control A
SAE R 15 / 4SH 1 piece fitting *	2"	2"	2"
SAE R15 / 4SH 2 piece fitting *	1 1/2"	1 1/2"	2"
SAE R12 / 4SP 2 piece fitting *	2"	2"	2"
Industrial	3"	3"	3"
90° Elbows	2"	2"	2"
Crimp range	100 mm	100 mm	102 mm
Opening	+ 41 mm	+ 41 mm	+40 mm
Opening without dies	143 mm	143 mm	143 mm
Master dies length (mm)	110 mm	110 mm	110 mm
Type of dies	239 - xx / 266	239 - xx / 266	239 - xx / 266
Speed (mm/sec)			
Close	20/1,1	30/1,5	30/2,3
Crimp	0,3	1,5	1,1
Open	6,5/30	8,7/30	15,4/30
Noise level	69 dBA	69 dBA	69 dBA
Drive	1,8 kW	3 kW	4 kW
Oil	4 L	35 L	50 L
L x W x H (mm)	505 x 430 x 490	600 x 550 x 750	700 x 550 x 710
Weight	145 kg	190 kg	260 kg
Options			
12 VDC / 24 VDC	✓	—	—
1 Phase	✓	✓	✓
3 Phase	—	✓	✓

* According to the fitting. ** Intermediate dies not required.


Type of dies		
239-xx-Ø-yy 266		
Ø mm	-mm-	-mm-
6,8	50	
9	50	
10	50	
12	65	
14	65	
16	65	
17	65	
19	65	
20	65	
22	65	
24	65	
26	65	
28	80	
30	80	
31	80	
32	80	
36	80	
38	80	
39	80	
40	80	
44	80	
47	100	
50	100	
54	100	
57	100	
62	100	110
67		110
71		110
74		110
78		110
84		110
86		110
92		110

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

Package



QDS 239 B



QDC 239.5

Package = Machine

+ PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71

+ 266.239L

+ QDC 239.5

+ QDS 239 B

